



*** Not suitable for sand, glass or other types of media.**

FILTER DETAILS



OC-1 MEDIA



- Fitted with 1" collector arms
- Laterals with an open line of 3mm



- Transparent lid with screws

ASTER OC-1 Filter Side

FEATURES

- ✓ Laminated filter manufactured with polyester resin and fiberglass.
- ✓ Internals with special laterals with an open line of 3mm.
- ✓ Filter for a Side multiport valve.
- ✓ Rotating diffuser for an easy filled of the filtration media.
- ✓ Filter for OC-1 media.
- ✓ Filter color: white
- ✓ 1/4" air and water drain.
- ✓ Transparent lid with screws.
- ✓ Maximum temperature: 50°C.
- ✓ Maximum pressure 2.5 bar.

TECHNICAL DATA

PACKAGING

Code	Model (mm)	Connections (mm/inch)		Filtering velocity (m³/h/m²)	Filtration Area (m²)	Flow (m³/h)	Maximum pressure (bar)	Swimming pool (m³)	Net weight (kg)	D (mm)	H (mm)	M (mm)	N (mm)	Units per pallet	Box dimension (cm)
		mm	inch												
68642-0100	450	50	1 1/2"	50	0.159	8	2,5	64	15	470	710	430	305	10	49x49x74
68643-0100	500	50	1 1/2"	50	0.196	10	2,5	72	15	520	705	415	290	8	56x56x85
68644-0100	600	50	1 1/2"	50	0.283	14	2,5	112	21	620	750	455	330	8	65x65x86
68645-0100	650	50	1 1/2"	50	0.332	17	2,5	120	22	670	805	495	370	8	70x70x89
68646-0100	750	63	2"	50	0.442	22	2,5	168	30	770	900	55	325	2	80x80x93
68647-0100	900	63	2"	50	0.636	32	2,5	240	48	920	1000	635	365	1	96x96x110
68648	900	75	2 1/2"	50	0.636	32	2,5	240	48	920	1000	660	390	1	96x96x110

MEDIA WEIGHT

Code	Volume OC-1	OC-1 (kg)
68642-0100	44	9
68643-0100	59	12
68644-0100	78	16
68645-0100	125	25
68646-0100	181	36
68647-0100	313	63
68648	313	63

