







AUTOMATIC REGULATION

Phileo VP automatically adjusts the pH of the water, in pH- or pH+ mode. Simply choose the setpoint value, Phileo VP does the rest.



RAPID DISPLAY

The dosing pump lights up according to the measurement and alerts. In an instant, you can clearly see the pH of your pool! Time saving and simplicity guaranteed all season!





Référence	Modèle
PF10J051	Phileo VP
PF10J050	Phileo POD VP



CONNECTED AND INTUITIVE

Control the pH regulation of your pool from anywhere in the world on **your smartphone** with an intuitive app that allows you to configure the Phileo VP but also set up notifications **for total peace of mind.**



RELIABLE AND EASY-TO-USE

The Phileo POD model is supplied with a compact measurement chamber ensuring **reliable pH readings and simplifying the hydraulic installation** of your appliance.

THE PH REGULATOR IS THE EASIEST TO INSTALL ON THE MARKET

No more filtration pump slaving without knowing where to connect! Phileo VP is supplied with a power cable for direct connection to a protected 230V socket.

The filtration status is captured by a flow rate sensor that gives a more reliable indication than a single filtration slaving.

To simplify installation, the Phileo POD model is supplied with a measurement chamber by gathering all the accessories required to treat pool water in a single location (sensor, injector, flow).







Measurement chamber Phileo POD VP only

INTUITIVE AND COMPLETE SETUP

The pH regulation can be set up in just a few minutes with the touch of just one button or via an intuitive smartphone app, offering additional features:

Available setup	Арр.	Device	
Mode selection (pH+ or pH-)			
Choice of setpoint value (6.8 to 7.6)	②	②	
Calibration of the pH 7.0 sensor	⊘	②	
Calibration of the 2-point sensor	②		
Manual adjustment of the measurement (+/- 0.3)	②		
Overdose alert setup	②		
Tank volume setup	②		
Remote setup	②		





PEACE OF MIND IN A GLANCE

The Phileo VP dosing pump is fitted with an RGB LED which lights up according to the different settings. This patented process, which is also used in the Zelia chlorinator, allows you to instantly view the pH value of the pool or the technical room and see if a corrective operation needs to be carried out.









Way off

Set-up	Couleui			
pH- mode	0			
pH+ mode	•			
Sensor calibration	• • •			
Daily control	Couleur			
Measuring error	•			

Maximum daily volume pH measurement







	ľ
-	1

Reference	Model	Power	Equipment supplied		Max. injection volume	Max. pump flow rate	Max. tank volume	Connection	Housing dimensions
PF10J051	Phileo VP	230V AC	pH sensor, calibra- tion Kit (bottle	3 x 50 mm clamp saddles	2 litres / jour	1.5 l/h	150 m³	Wifi (local and remote)	130 x 115
PF10J050	Phileo POD VP		+ solution), injection kit	Zelia Pod measure- ment chamber	Réglable	1.5 1/11	1301119	/ Bluetooth®	x 35 mm





