

GALACTIC MONOBLOCK

PRO RANGE OF FILTRATION UNITS



Professional, versatile filtration unit for in-ground and above-ground pools.


Includes a **filter** made of high-strength blown thermo-plastic, a 6-port **multiport valve** and a self-priming **pump**.

Wide **range of filtration rates**: flow rates from 5 m³/h to 14 m³/h.

Includes all accessories for **complete, quick installation**.

CONDITIONS OF USE

Intended uses:	Swimming pool and spa water filtration
Maximum water temperature:	35°C
Normal operating pressure:	0.6-1.4 bar
Maximum pressure:	2.4 bar
Filter medium:	Sand or glass
Filter medium particle size:	0.4-0.8 mm



Quick and easy installation.



Outstanding pro service.




Versatility: for installation in above-ground or in-ground pools.

GALACTIC MONOBLOCK

PRO RANGE OF FILTRATION UNITS



Complies with Standard
EN 16713-01



Connections:

Connections included for $\varnothing 38\text{mm}$ and $\varnothing 50\text{mm}$ on filter and pump.



Self-priming pump:

With built-in strainer and cable with plug for quick installation. Water bleeder included.



Top valve:

6-port valve for filtration, backwashing, rinsing, recirculation, emptying and closing operations.



Pressure gauge and air bleeder:

Pressure gauge and air bleeder included in the valve.



Filter body:

Highly resistant filter body in anthracite gray and high-quality finishes. Easy top access via a locking band. Water bleeder included.



Accessories:

All accessories are included for complete, quick installation: base, flexible hose and hardware.

*Sand or glass filter medium not included

TECHNICAL SPECIFICATIONS

REF.	FLOW RATE m ³ /h	Ø FILTER mm	PUMP POWER HP	Ø CONNECTIONS mm	SAND kg*	DIMENSIONS (mm)					PACKAGING	
											WEIGHT Kg	DIMENSIONS mm
						Ø	A	B	C	D		
74471	5	380	1/3	38 / 50	40	380	860	710	635	295	20	790x600x700
74472	6	400	1/3	38 / 50	40	400	905	710	650	295	20.5	
74473	8	500	1/2	38 / 50	100	500	975	830	740	295	24	
74474	10	500	3/4	38 / 50	100	500	975	830	740	295	25.5	870x600x715
74475	12	600	3/4	38 / 50	150	600	1030	830	816	295	29	
74476	14	600	1	38 / 50	150	600	1030	830	816	295	30	

